

To provide moisture resistance and a decorative finish on concrete or masonry



CONSUMER PRODUCTS

THOROSEAL® WATERPROOFING PAINT

Thoroseal® Waterproofing Paint is a waterbased ready-mixed, latex-formulated coating designed to provide a dense, waterproof barrier for vertical concrete and masonry surfaces. This versatile coating has super adhesion qualities when applied to basement walls, retaining walls, brick, cinder and concrete block, above or below-grade concrete, plaster, masonry and stucco. It resists abrasion, weathering, peeling and delamination, and is guaranteed to damp proof. Available in White only.

Weather & Drying Guidelines

Thoroseal® Paint may be applied to slightly damp or (for best results) warm, dry surfaces using a quality synthetic bristle brush or roller. Allow a minimum of 3 hours drying time before applying second coat (24 hours drying time before topcoating).

Application Suggestions

Run a test patch in an inconspicuous area to ensure proper adhesion, drying and coloration. Apply as shown. Thoroseal® Paint may be applied by brush, roller or spray.

Clean & Prepare Surface

Remove all dirt, loose particles or white powdery deposits (efflorescence) from surface, plus any substance that may prevent maximum adhesion such as paint or oil. Use a mild solution of bleach and water (1 qt. to 5 gals) to remove any mildew, mold or algae from surface. Do not use detergents. A thorough cleaning may include power washing. Patch any holes or cracks (including open joints) with Thoro Waterplug®.

Stir Paint Thoroughly

Stir Thoroseal® Paint well, prior to and periodically during application. DO NOT THIN.

A Two-Coat System

Thoroseal® Waterproofing Paint is a two-coat system that can be applied to slightly damp or (for best results) dry surfaces using a brush or roller. Allow a minimum of 3 hours drying time before applying second coat, 24 hours before topcoating. If moisture penetration continues, additional coats may be required to seal any pores or



pinholes. Coverage: Rough Surface - first coat 75 sq. ft./gal. Smooth Surface - first coat 100-125 sq. ft./gal. Additional coats 125 sq. ft./gal. For specific application or sprayer guidelines, call 1 (216) 839-7171 or go to www.thoroproducts.com.

Clean-Up, Storage, and Disposal

Clean tools and small spills with warm soapy water immediately after use. Store unused product in its original can, tightly sealed. Protect from freezing. Dispose of this product in accordance with local, state and federal requirements.



Thoro Consumer Products • BASF Construction Chemicals, LLC • 23700 Chagrin Blvd. • Cleveland, Ohio 44122
phone 216-839-7171 or 866-518-7171 • fx 216-839-8833 or 866-494-8833 • ThoroProducts.com