

For a waterproof, cement-based, white decorative finish on concrete or masonry



CONSUMER PRODUCTS

# SUPER THOROSEAL® WATERPROOF COATING

Super Thoroseal® Waterproof Coating is a powder, cement-based waterproofing product for protecting concrete and masonry substrates. Easy to use, just add water. Coating can be applied to interiors and exteriors, above or below ground. Weatherproofs, seals out dampness with long lasting, decorative white finish. Resists low level hydrostatic pressures, stops seeping water and cuts radon gas infiltration. Ideal for basement, foundation and retaining walls, concrete planters and walls, stucco, concrete and cinder block, brick, sea walls and piers.

## Weather Guidelines

Do not apply to frozen or frost covered walls, or when ambient temperature is below 40°F.

## Application Suggestions

Thoroughly dampen the surface to make application of Super Thoroseal® Coating easier. Apply as shown. Use a tampico fiber brush to apply a thick coat. Coverage: 35 lb. container covers up to 105 sq. ft., depending on porosity and texture.

## Clean & Prepare Surface

Remove all dirt, loose particles or white powdery deposits (efflorescence) from surface, plus any substance that may prevent maximum adhesion such as paint or oil. Use a mild solution of bleach and water (1 qt. to 5 gals) to remove any mildew, mold or algae from surface. Patch any holes or cracks (including open joints) with Thoro Waterplug®.

## Mix Thoroughly

Mix with clean water to a thick "pancake batter" consistency. No more than 1¾ quarts of water per 10 pounds of powder. The brush will stand up in the mixing container when the proper consistency is reached. Let the mixture soak for 15 minutes to fully activate the waterproofing elements. Use within 40 minutes.

## Brush it On

Thoroughly dampen surface. Start at the top and work down. Use a tampico fiber brush to apply Super Thoroseal® in a thick coat, working the mixture into the pores of the surface for a good penetrating seal. Double back and use the brush to smooth out the material.



*Must NOT be applied to painted surfaces.*



Allow 12 hours between coats for drying time. Lightly dampen wall before applying second coat. Check the mix from time to time for dryness; add just enough water to keep the mix at proper consistency. Use brush to make swirls or textures, if desired. For specific application guidelines, call 1 (216) 839-7171.

## Clean-Up, Storage, and Disposal

Clean tools and small spills with warm soapy water immediately after use. Store unused product in its original can, tightly sealed. Protect from freezing. Dispose of this product in accordance with local, state and federal requirements.



Thoro Consumer Products • BASF Construction Chemicals, LLC • 23700 Chagrin Blvd. • Cleveland, Ohio 44122  
phone 216-839-7171 or 866-518-7171 • fx 216-839-8833 or 866-494-8833 • ThoroProducts.com