

Cost-effective, durable repair mortar for horizontal concrete surfaces



CONSUMER PRODUCTS

# THORO<sup>®</sup> CONCRETE PATCH & REPAIR

Thorocrete<sup>®</sup> Concrete Patch is a one-component, dry polymer-modified cement-based patching material, stronger than concrete. Easy to use, just add water. Dries twice as fast as mortar. Matches the color of concrete. Used for patching, resurfacing or leveling interior or exterior concrete floors, residential driveways, sidewalks, curbs, steps and patios.

## Weather & Drying Guidelines

Thorocrete<sup>®</sup> Concrete Patch is designed to dry fast - twice as fast as mortar. Actual drying time depends on ambient temperature as well as the temperature of the powder, mixing water and affected surface.

## Application Suggestions

Apply as shown. Use a tampico fiber brush to apply and a trowel to place thickened mixture. Wear protective gloves and goggles.

## Clean & Prepare Surface

Remove all dirt, loose material, grease and unsound concrete. Use a mild solution of bleach and water (1 qt. to 5 gals) to remove any mildew, mold or algae from surface. A thorough cleaning may include power washing. Make sure surface is structurally sound.

## Mix Thoroughly

Mix Thorocrete<sup>®</sup> powder with clean water to form a stiff workable consistency. Stir until all material is thoroughly wet and no dry lumps remain.

## Brush/Trowel it On

Apply a thin coat with a tampico fiber brush, working it into the area to be patched (up to 1/4 " thick). Using a trowel, place another coat of Thorocrete<sup>®</sup>, (no more than 1/2" thick, in the application area, while first coat is still wet. Coverage: 3 lbs. covers approximately 1-1/2 sq. ft, 1/4 inch thick (1.36 kg covers approximately .21 sq.m, .64 cm thick). For specific application guidelines, call 1 (216) 839-7171 or go to [www.thoroproducts.com](http://www.thoroproducts.com)



## Clean-Up, Storage, and Disposal

Clean tools with warm soapy water immediately after use. Store unused product in its original can, tightly sealed. Dispose of this product in accordance with local, state and federal requirements.



Thoro Consumer Products • BASF Construction Chemicals, LLC • 23700 Chagrin Blvd. • Cleveland, Ohio 44122  
phone 216-839-7171 or 866-518-7171 • fx 216-839-8833 or 866-494-8833 • [ThoroProducts.com](http://ThoroProducts.com)