

SUPER THOROSEAL® WATERPROOF COATING

For a waterproof, cement-based, white decorative finish on concrete or masonry



CONSUMER PRODUCTS

Features and Benefits:

- White, dry-polymer-modified coating
- Excellent adhesion, flexural strength, durability and freeze/thaw resistance
- Weatherproofs and seals out dampness.
- Stops seeping water and cuts radon gas infiltration.
- Ideal for interior or exterior, above or below grade.
- Fills and seals pores and voids to correct surface irregularities.
- Protects concrete, masonry, stucco, and foam substrates.
- Becomes part of the wall when fully cured.
- Long-lasting decorative white finish.
- Resistant to mold and mildew.
- Apply thickly with tampico fiber brush.
- Easy to use. One-component powder mixes easily with water.
- Cleans up with soap and water immediately after use.

Warranty:

- 10 years. **Two Coats Necessary.** Must NOT be applied to painted surfaces.
- Full warranty details at ThoroProducts.com.

Recommended for:

- Basement Walls
- Foundation and Retaining Walls
- Concrete Planters and Walls
- Concrete and Cinder Block
- Brick
- Stucco
- Sea Walls and Piers

Use WATERPLUG® Hydraulic Cement prior to application to:

- Seal out moisture and prevent leaks.
- Patch holes or cracks, including open joints.

Yield Per 35-pound pail:

- Base coat: 155 square feet at 1/16 inch dry-film thickness
- OR Top coat: 310 square feet at 1/32 inch dry-film thickness
- Coverage will vary depending on surface texture and porosity.



Ship weight is gross U.S. pounds

Item Number	Color	Single Unit Net Wt.	Single Unit UPC Code	Unit Ship Weight	Units per Pallet	Pallet Ship Weight
T5010	White	35 lb. Pail	0 80492 05010 3	38	36	1,368